

2017 Great Dane Dry Van

Stock #
T2107
T2108



SPECS

- CS1 tandem axle
- 2 units available
- 53'
- Disc Brakes
- 11R22.5 tires
- Steel wheels

2017 Great Dane Dry Van



Great Dane

Dimensions

- Exterior 53' long x 102" wide

Suspension

- Henderickson HKANT 40K
- Air suspension on slider
- Dump valve and suspension gauge in weatherproof box

Brakes

- Bendix disc brakes

Tires & Rims

- 8 Bridgestone 11R22.5"
- R197 Tires
- 8 Steel wheels

Wheel Ends

- Parallel large bearing grease bath wheel hubs and Hubometer
- 6 year wheel end warranty

Coatings

- Front & side sheets pre-painted white
- Rear doors & frame painted white
- Rear impact guard hot dipped galvanized
- CorraGuard coated under carriage and landing gear

HENDERICKSON
For The Road Ahead



Features

- Lightweight tandem slider
- Optimized for dry-freight and refrigerated vans
- Lightest 40,000-lb. capacity air suspension in the industry
- 40,000-lb. capacity

Performance, durability and long service life are hallmarks of Bendix air disc brakes – and they're the lightest weight available.

Bendix

With longer pad service intervals and faster maintenance than drum brakes, air disc brakes help reduce maintenance costs and downtime.



BRIDGESTONE

- Deep tread depth for high-scrub trailer service.
- Wide, solid shoulder ribs resist tearing and fight turning side forces.
- Computer-designed belt package protects against side forces encountered on spread and multi-axle trailers.
- Tough tread compounds fight scrub wear, yet run cool for long mileage.



CorroGuard
PROTECTION

A spray-in-place thermoplastic coating engineered for long-term protection from road abrasion, impact, and corrosion.

CorroGuard offers chemical and corrosion resistance as well as a superior impact resistance to withstand the toughest road conditions.

2017 Great Dane Dry Van



Great Dane

Interior

- Front scuff/bulkhead 12ga
- Carbon steel welded to coupler plate
- Side scuff HDPE black plastic 5/8" X 12"
- Polyethylene side lining between up rights
- Floor 1.38" Prolam hardwood, undercoated front 10' and rear 18'
- Vertical logistic posts on 16" centers
- .125" X 24" Diamond Threshold plate

Exterior

- .50" aluminum side sheets
- Logistic posts 16" centers
- Bottom extruded aluminum rubrail 17" up from lower edge
- Endurguard rear door frame
- .50" composite swing doors with galvanized steel cover sheet all painted white
- 1" roof bows on 24" centers

Lighting & Wiring

- 4-LED rear tail, stop/turn lights
- Midship turn signal 2 front corner marker lights, 3 top rear with 1 top rail marker
- Grote wiring harness with 10 year warranty

Understructure

- 36" Kingpin 3.50" channel upper coupler with stainless roll up.
- GD 60 no lube 10 year warranty landing gear
- All crossmembers steel and on 12" centers

EnduroGuard

Engineered with a combination of galvanized carbon steel and stainless steel components, EnduroGuard delivers corrosion resistance and superior appearance over other coating types.

Unlike galvanized coating, galvanneal will not crack, flake or discolor, and provides an integrated zinc surface that readily accepts our high-performance paint system.

Stainless steel is used in the high impact areas of the frame for protection against corrosion where you need it the most.

Grote



Get in touch

Bill Tait
Trailer Sales Manager
902.698.3993
btait@novatrucks.ca